

PRECAUTIONS:

Avoid skin contact, wash thoroughly after handling. Do not get in eyes. Wear protective eye wear when handling. Store in a cool, dry, ventilated area.

FIRST AID:

EYES: Rinse thoroughly with water for at least 15 minutes. Seek medical attention.

SKIN: In case of skin contact, rinse skin thoroughly with water.


INGESTION: If swallowed, dilute by drinking milk or water. Do not induce vomiting. Seek medical attention immediately.

INHALATION: Avoid inhalation. If inhalation occurs, remove individual to fresh air, give artificial respiration, call a physician.

KEEP OUT OF REACH OF CHILDREN

Consult material safety data sheet before using. For commercial, industrial and institutional use only.

REFER TO MATERIAL SAFETY DATA SHEET



Rig Wash

Heavy Duty Rig Wash

Contains Water Softeners, Emulsifiers,
Wetting Agents & Foaming Agents

Dissolves in Hot & Cold Water
Biodegradable

L

bullfrogproducts.ca

Lot #

FEATURES

Rig Wash is a quality granular washing compound containing water softeners, emulsifiers, wetting agents and foaming agents.

Rig Wash may be used for different washing purposes encountered in the oilfield and may be used on all paints and finishes, rubber, chrome, glass, and stainless steel at recommended use dilutions.

DIRECTIONS

Floors & Walls:

Dilute 1 part **Rig Wash** to 10 - 40 parts water. Spray surface and wipe with a cloth.

Heavy Grease, Oil & Soil Removal Ect.:

Dilute 1 part **Rig Wash** to 2 parts water.

Pressure Washers:

Add to automatic feed system at a rate of 1 part **Rig Wash** to 40 parts water.

Auto Scrubbers:

Dilute 1 part **Rig Wash** to 10 - 40 parts water.

St. Albert, AB T8N 6C1

Toll Free: 1-866-543-5276